

ELIMINATOR MODULAR MACHINES GENERAL SPECIFICATIONS				
Height Clearance	Standard: 42" (1066 mm) Optional: 48" (1219 mm) Optional: 54" (1371 mm) Optional: 60" (1524 mm)			
Y Axis Travel	120" (3048 mm)	144" (3658 mm)	168" (4267 mm)	200" (5080 mm)
X Axis Travel	245" (6223 mm)	317" (8052 mm)	388" (9855 mm)	460" (11684 mm) 531" (13487 mm) 603" (15316 mm)
Z Axis Travel	40" (1016 mm)	40" (1016 mm)	40" (1016 mm)	40" (1016 mm)
Spindle-to-Table Distance	4"-44" (101-1118 mm)	4"-44" (101-1118 mm)	4"-44" (101-1118 mm)	4"-44" (101-1118 mm)
Automatic Tool Changer	40 Tools	40 Tools	40 Tools	40 Tools
CNC System	Fanuc 31i	Fanuc 31i	Fanuc 31i	Fanuc 31i
SPINDLE SPECIFICATIONS				
Speed Range	0 – 6000 rpm	0 – 6000 rpm	0 – 6000 rpm	0 – 6000 rpm
Gear Box	4:1 2 speed	4:1 2 speed	4:1 2 speed	4:1 2 speed
Main Drive Power	49 hp (37 kW)	49 hp (37 kW)	49 hp (37 kW)	49 hp (37 kW)
Z-Axis Feed Thrust	5,000 lb (22 kN)	5,000 lb (22 kN)	5,000 lb (22 kN)	5,000 lb (22 kN)
Spindle Nose	CAT50	CAT50	CAT50	CAT50